



Model	A	B	C	D	E	F	G	H
HE 30	47	39	65	5	70	20	50	60
HE 60	47	39	65	5	70	20	50	60
HE 100	47	39	145	5	70	20	50	60
HE 150	47	39	195	5	70	20	50	60

## HE

### ANTI-CONDENSATION HEATERS

- Heaters designed to prevent condensation and to ensure a minimum operating temperature in the control cabinets;
- They are a valid support for the correct functioning of the other electric components in the control cabinet;
- Made of extruded aluminium anodised with a PTC resistor inside;
- Energy saving;

- Cage clamp connectors for quick and easy wiring: with stranded wire 0,5 -1,5 mm<sup>2</sup>; with rigid wire 0,5 - 2,5 mm<sup>2</sup>;
- Clip for 35 mm DIN rail;
- Storage temperature range: -40 ÷ 80°C;
- Operating temperature range: -40 ÷ 70°C;
- Vertical mounting position (with bottom connection terminals).

### TECHNICAL DATA

Model	Code	Voltage (V AC/DC)	Power nom. (W)	Nom. Curr. (A)	Starting current (A)	IP Grade	Weight (Kg)
HE 30	0086000	110-250	30	0,25	1,5	IP20	0,3
HE 60	0086010	110-250	60	0,32	1,5	IP20	0,4
HE 100	0086020	110-250	100	0,58	2	IP20	0,5
HE 150	0086030	110-250	150	0,66	2,5	IP20	0,7

### INSTALLATION EXAMPLE

